

1/3" CCD COLOR VIDEO CAMERA TK-C9200UA



IVC

BFLOCK

600 TV Lines Easy Day/Night

Lens not included



■ High-Resolution of 600 TV Lines

Newly developed **14bit** DSP enables industry-leading high quality pictures

■ Super LoLux[™] Sensitivity

0.05 lx at color mode (50% video level, F1.2, AGC HIGH) 0.03 lx at B&W mode (50% video level, F1.2, AGC HIGH)

Industry-leading S/N Ratio of 52dB

3D Noise Reduction

Powerful system to reduce noise in dark environments

Up to 128x of Slow Shutter

Increases visibility even in low light situations

Area White Balance

New function that can apply Auto White Balance to a specific area

Black Level Adjustment

Intelligent adjustment for dark areas to provide images without black out

Easy Installation with Well-Conceived Menu

Combination of DIP switch and built-in Menu makes detailed settings simple and easy

Variety of Functions for Precise Monitoring

- Automatic Gain Control (AGC)
- Automatic Electronic Shutter (AES)
- 4 Area Patterns for Backlight Compensation (BLC)
- Manual and Auto Tracking White Balance
- 1.4x/2.0x Digital Zoom
- Privacy Mask for protecting against intrusive monitoring
- Display Mode Selection for CRT and LCD
- CCD White Spot Compensation
- Focus Adjustment Mode for accurate focusing
- 24VAC/12VDC Dual Voltage

■ Eco-Friendly Super Low Power Consumption Approx. 40% lower than conventional models

Full-Fledged Surveillance Camera with High-Resolution Images and Clear Colors in Any Situation

Specifications

Super LoLux[™] "COLOR IN VIRTUAL ZERO LUX"

This camera has been designed to assure precise color reproduction in low light situations. It is possible to identify image colors in much darker places.





Normal camera

3D Noise Reduction (3DNR)

3DNR is the powerful method to improve image quality even though it's shot in the dark. Noise data is detected by comparing some continuous frames and reduced by blending it into other frames over time.





Area White Balance

Auto White Balance can be applied to a designated area. With this, color casting can be prevented by setting the white balance within an area while avoiding strong color zones.



Focus Adjustment Mode

Focus Adjustment mode opens the iris fully for 30 seconds to make it easier to adjust focus by temporarily reducing the depth of field.



DISTRIBUTED BY



		TK-C9200UA
Signal system	NTSC	
Image device	1/3 type IT CCD	
Number of effective pixels	380,000 (768H x 494V)	
Sync system	Internal	
Scanning system	2:1 interlace, 525 lines	
Scanning frequency	15.734kHz (H), 59.94Hz (V)	
Video output	Composite video signal: 1.0V (p-p), 75 ohms (BNC)	
Video S/N ratio	52 dB (AGC off)	
Horizontal resolution	600 TV lines *	
Minimum illumination (typical)	0.05 lx (50%, F1.2, AGC HIGH) 0.025 lx (25%, F1.2, AGC HIGH)	
B&W mode	0.03 lx (50%, F1.2, AGC HIGH) 0.015 lx (25%, F1.2, AGC HIGH)	
Iris control	DC iris	
White balance	ATW (wide/narrow) / AWC / Manual (ATW color temp. range 2300K to 10,000K)	
Day/Night	Easy D/N	
3DNR	NORMAL / HIGH	
Display mode (Monitor type)	LCD1/LCD2/CRT	
BLC	off/on (4 patterns)	
AGC	OFF/MID/HIGH	
AES	off/on (1/60s to 1/100,000s)	
Sens-up	off / x2 to x128	
Digital zoom	x1, x1.4, x2	
Privacy mask	4 areas	
Focus adjustment mode	Yes	
Lens mount	CS	
Power supply	24VAC (60Hz) / 12VDC UL listed	
Power consumption	2.3 W	
Operating temperature range	14°F to 122°F (-10°C to 50°C) (32°F to 104°F (0°C to 40°C) recommended)	
Dimensions (WxHxD)	2-3/16" x 2-7/16" x 5" (55mm x 61mm x 126mm)	
Weight (approx.)	0.6lbs (270g)	

Dimensions

Unit: inch (mm) 5 (126) 4-1/2 (114.3) JVC 2-1/8 (53) 1-3/8 5/16 (7.8) 1/4 20 UNC MOLINTING HOLE

Note: Screen images are explanatory purpose and not actual images attained using this product. All brand or product names may be trademarks and/or registered trademarks of their respective owners. Copyright © 2011, Victor Company of Japan, Limited. All Rights Reserved.

Design and specifications subject to change without notice.



Hachioji Business Centre of Victor Company of Japan, Ltd. has received ISO14001 Certification for environmental management and ISO9001 Certification for quality assurance management.

Printed in Japan KCN-1858C TK-C9200U 2011/3

"JVC" is the trademark or registered trademark of Victor Company of Japan, Limited.

* Tamron M13VM246 at wide angle

TK C020011A